(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 4 November 2004 (04.11.2004)

PCT

(10) International Publication Number WO 2004/094069 A1

(51) International Patent Classification7: B05B 1/04, 1/02

(21) International Application Number:

PCT/US2004/003323

(22) International Filing Date: 5 February 2004 (05.02.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/320,103

11 April 2003 (11.04.2003) US

(71) Applicant (for all designated States except US): NORD-SON CORPORATION [US/US]; 28601 Clemens Road, Westlake, Ohio 44145 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KOSOVICH, Deborah [US/US]; 1009 Scituate Ct., Grafton, Ohio 44044 (US).

(74) Agent: MCKNIGHT, Douglas B,; CALFEE, HALTER & GRISWOLD LLP, 800 Superior Avenue, Suite 1400, Cleveland, Ohio 44114 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


- of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AIRLESS SPRAY NOZZLE



(57) Abstract: An airless spray nozzle tip (10) for use in coating workpieces such as containers includes a first groove (40) located on one side (24) of the tip, and second (30), third (32) and fourth (34) grooves located on the other side of the tip, thereby forming three orifices in the nozzle tip (10). The nozzle tip (10) produces a generally circular spray pattern with a diameter of at least about one half inch, at a distance in the range of from about one inch to about three inches from the nozzle tip, and at a flow rate at or below about 0.045 galloons per minute. A process of coating a workpiece, such as a container, includes spraying liquid from a nozzle tip to procuce this generally circular pattern, the nozzle tip preferably having three orifices.